

Machine Series: **Orbital Wrapper**

Horizontal Stretch Wrapper (semi-automatic)

Technical Details:

- Double film roll support
- Adjustable tension
- Automatic overrun brake
- Safety foot switch

Speed:
Up to 150 rpm



Model:	HZSW-50	HZSW-90	HZSW-125	HZSW-160	HZSW-200/250
Speed:	150 rpm	90 rpm	65 rpm	50 rpm	55 rpm
Frequency converter:	Omron	Omron	Fuji, Omron	Fuji, Omron	Fuji, Omron
Power Supply:	230 V I	230 V I	230 V I, 230/400 V III+N	230 V I, 230/240 V III+N	230 V I, 230/240 V III+N
Power Consumption:	0,4 kW / 0,26 kW	0,75 kW / 0,31 kW	1,5 kW / 0,48 kW	1,5 kW / 0,52 kW	1,5 kW / 0,55 kW
Air Pressure:	6 bar	6 bar	6 bar	6 bar	6 bar
Film Thickness:	23 my	23 my	23 my	23 my	23 my
Dimensions of the Film Roll (L x W x H):	100x200x38 mm*	100/166x230x38 mm*	100/166/255x230x38 mm*	100/166/250x230x38 mm*	100/166/250x230x38 mm*

Horizontal Stretch Wrapper (automatic):

Technical Details:

- Double film roll support
- Adjustable tension
- Automatic overrun brake
- Automatic film take up
- Automatic film cutting system
- Light barrier for automatic cycle start
- Touch screen for parameter settings
- Program memory



Model:	HZSW-A-50	HZSW-A-90	HZSW-125	HZSW-160	HZSW-200/250
Speed:	180 rpm	100 rpm	80 rpm	60 rpm	55 rpm
Speed Conveyor Rolls:	30 m/min	15 m/min	15 m/min	15 m/min	15 m/min
Frequency Converter:	Fuji / Omron	Fuji / Omron	Fuji, Omron	Fuji, Omron	Fuji, Omron
Power Supply:	230 V	230 V	230/400 V III+N	230/240 V III+N	230/240 V III+N
Power Consumption:	1,25 kW / 0,64 kW	1,50 kW / 0,97 kW	3,0 kW / 1,61 kW	3,0 kW / 1,63 kW	3,0 kW / 1,66 kW
Air Pressure:	6 bar	6 bar	6 bar	6 bar	6 bar
Film Thickness:	23 my	23 my	23 my	23 my	23 my
Film Roll Dimensions (L x W x H):	100x200x38 mm*	100/166x230x38 mm*	100/166/250x230x38 mm*	100/166/250x230x38 mm*	100/166/250x230x38 mm*